



Material Safety Data Sheet

Albi 490W Primer

Albi Manufacturing

Division of StanChem, Inc.
401 Berlin St., East Berlin, CT 06023
Emergency Telephone Number: CHEMTREC 1-800/424-9300
Information Telephone Number: 860/828-0571
Date of Preparation: 2/4/08

Section I - Product Identification

Product Number: 15X0505
Product Name: Albi 490W Primer
Product Class: Acrylic Water Base

Section II - Hazardous Ingredients

Ingredient	Percent Wt.	Occupational Exposure Limits				Skin	Vapor Pressure @20°C (mmHg)
		ACGIH TLV (ppm)	ACGIH TWA (ppm)	OSHA STEL (ppm)	Ceiling (ppm)		
Butyl Cellosolve CAS #[111-76-2]	4.6		20				0.4

Section III - Physical Data

Boiling Range: 199°F
Vapor Density: Heavier Than Air
Evaporation Rate: Slower Than Butyl Acetate
VOC Content (g/l): 161.3
Weight per Gallon: 10.4 – 11.4 #/gal

Section IV - Fire and Explosion Hazard Data

Flammability Classification:

OSHA: Combustible Liquid - Class IIIA
DOT: Combustible Liquid
Flash Point: N/A

Extinguishing Media: Foam Alcohol Foam CO₂ Dry Chemical Fog

Unusual Fire and Explosion Hazards: Water may be used to cool containers to prevent pressure build-up and possible rupture from exposure to extreme heat.

Special Firefighting Procedures: Fight as volatile liquid fire. Closed containers may rupture when exposed to extreme heat. Use water to keep fire exposed containers cool to reduce the pressure.

